



DIONE IP20

- Flat installation depth
- Incl. dimmable power supply unit and connection box
- Feed-through wiring possible
- Ideal refurbishment solution
- Light and power supply unit with adapter plug

Housing	Aluminium	Required Installation	25 mm
Height	41 mm	Depth	
Ø	82 mm	Light Beam Angle	36 Degree
Power	8.5 W	Swivelling Angle	30 Degree
Rated Input Voltage	220-240 V/AC	Cut Out Ø	68 mm
Power Supply Unit incl.	Yes	Control	Leading-edge dimmer, Trailing-edge dimmer
Installation Depth	38 mm		

Article	Housing Color	Colour Temperature	Luminous Flux	Colour Rendering Index (Ra)	Price
565375	White	2700 K	750 lm	81	€ 59.95
565376	Silver	2700 K	750 lm	81	€ 59.95
565377	Black	2700 K	750 lm	81	€ 59.95
565378	Nickel	2700 K	750 lm	81	€ 59.95
565379	Chrome	2700 K	750 lm	81	€ 59.95
565355	White	3000 K	800 lm	81	€ 59.95
565356	Silver grey	3000 K	800 lm	81	€ 59.95
565357	Black	3000 K	800 lm	81	€ 59.95
565371	Nickel	3000 K	800 lm	81	€ 59.95
565372	Chrome	3000 K	800 lm	81	€ 59.95
565358	White	4000 K	800 lm	84	€ 59.95
565359	Silver grey	4000 K	800 lm	84	€ 59.95
565360	Black	4000 K	800 lm	84	€ 59.95
565373	Nickel	4000 K	800 lm	84	€ 59.95
565374	Chrome	4000 K	800 lm	84	€ 59.95



Accessories

930863	Reflector 60° for Dione light series		€ 5.95
930864	Frosted diffusing lens for Dione lamp series		€ 2.95
829063	Safety spacer		€ 5.95