




DIONE IP20 DTW




- Flat installation depth (25 mm)
- Incl. dimmable power supply unit and connection box
- Feed-through wiring possible
- Ideal refurbishment solution
- Light and power supply unit with adapter plug

Housing	Aluminium	Required Installation	25 mm
Colour Temperature	1800-3000 K	Depth	
Luminous Flux	480 lm	Light Beam Angle	36 Degree
Height	41 mm	Swivelling Angle	30 Degree
Ø	82 mm	Cut Out Ø	68 mm
Power	8.5 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	Colour Rendering Index (Ra)	95
Power Supply Unit incl.	Yes		
Installation Depth	38 mm		

Article	Housing Color		Price
565380	<input type="checkbox"/> White	ww	€ 69.95
565381	<input type="checkbox"/> Silver	ww	€ 69.95
565382	<input type="checkbox"/> Black	ww	€ 69.95
565383	<input type="checkbox"/> Chrome	ww	€ 69.95
565384	<input type="checkbox"/> Nickel	ww	€ 69.95



Accessories

930863	Reflector 60° for Dione light series		€ 5.95
930864	Frosted diffusing lens for Dione lamp series		€ 2.95
829063	Safety spacer		€ 5.95

