




DIONE IP44 DTW

- Flat installation depth
- Splash-proof (downwards after installation)
- Including dimmable power supply and connection box
- Feed-through wiring possible
- Ideal refurbishment solution
- Light and power supply unit with adapter plug

Housing	Aluminium	Required Installation Depth	27 mm
Colour Temperature	1800-3000 K	Light Beam Angle	36 Degree
Luminous Flux	480 lm	Swivelling Angle	30 Degree
Height	41 mm	Cut Out Ø	68 mm
Ø	82 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Power	8.5 W	Colour Rendering Index (Ra)	95
Rated Input Voltage	220-240 V/AC		
Power Supply Unit incl.	Yes		
Installation Depth	41 mm		

Article	Housing Color		Price
565403	<input type="checkbox"/> White	ww	€ 74.95
565404	<input type="checkbox"/> Silver	ww	€ 74.95
565405	<input type="checkbox"/> Black	ww	€ 74.95
565406	<input type="checkbox"/> Chrome	ww	€ 74.95
565407	<input type="checkbox"/> Nickel	ww	€ 74.95



Accessories

930863	Reflector 60° for Dione light series		€ 5.95
930864	Frosted diffusing lens for Dione lamp series		€ 2.95
829063	Safety spacer		€ 5.95

