



SMD-68-230V-ROUND

- Integrated power supply unit
- swivelling
- low installation depth

Housing	Plastic	Light Beam Angle	45 Degree
Height	43.8 mm	Swivelling Angle	36 Degree
Ø	85 mm	Cut Out Ø	68 mm
Power	6.5 W	Control	Leading-edge dimmer, Trailing-edge dimmer
Rated Input Voltage	220-240 V/AC	Colour Rendering Index (Ra)	80
Power Supply Unit incl.	Yes		
Installation Depth	41.3 mm		

Article	Housing Color	Colour Temperature	Luminous Flux	EEL	Price
565337	<input type="checkbox"/> White	2700 K	510 lm		€ 19.95
565385	<input checked="" type="checkbox"/> Black	2700 K	510 lm		€ 19.95
565338	<input type="checkbox"/> White	3000 K	540 lm		€ 19.95
565386	<input checked="" type="checkbox"/> Black	3000 K	540 lm		€ 19.95
565339	<input type="checkbox"/> White	4000 K	550 lm		€ 19.95
565387	<input checked="" type="checkbox"/> Black	4000 K	550 lm		€ 19.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.