




COB 68 IP65




- Ideal for damp rooms
- Can be individually combined with power supply unit [excl.]

| | | | |
|-------------------------|------------|-----------------------------|---|
| Housing | Aluminium | Light Beam Angle | 45 Degree |
| Height | 44 mm | Cut Out Ø | 68 mm |
| Ø | 78 mm | Control | Dimmable via optional power supply unit |
| Power | 6.5 W | Colour Rendering Index (Ra) | 80 |
| Rated Input Voltage | 17-18 V/DC | Rated Current | 350 mA |
| Power Supply Unit incl. | No | | |
| Installation Depth | 46 mm | | |

| Article | Housing Color | Colour Temperature | Luminous Flux | Price |
|---------------|--------------------------------|--------------------|---------------|----------------|
| 565108 | <input type="checkbox"/> White | ww 2700 K | 670 lm | € 59.95 |
| 565110 | <input type="checkbox"/> White | nw 4000 K | 730 lm | € 59.95 |



Accessories

| | | | |
|---------------|-----------------------------|---|----------------|
| 829063 | Safety spacer |  | € 5.95 |
| 180512 | BASIC, CC, CC35018/18W |  | € 23.95 |
| 862202 | BASIC, DIM, CC, D35009UF/9W |  | € 28.95 |