



### COB 68 ACRYL

- Acrylic glass ring
- Discreet side lighting

Housing	Aluminium	Installation Depth	50 mm
Colour Temperature	2700 K	Light Beam Angle	30 Degree
Luminous Flux	675 lm	Cut Out Ø	62 mm
Length	78 mm	Control	Dimmable via optional power supply unit
Height	53.5 mm	Colour Rendering Index (Ra)	80
Ø	78 mm	Rated Current	350 mA
Power	6.5 W		
Rated Input Voltage	18-20 V/DC		
Power Supply Unit incl.	No		

Article	Housing Color		Price
<b>565195</b>	Silver		<b>€ 65.95</b>

CC

IP20

1 CH

A  
↑  
G

G



### COB 68 ACRYLIC HCL

Housing	Aluminium	Installation Depth	43 mm
Colour Temperature	2400-6500 K	Light Beam Angle	45 Degree
Luminous Flux	590 lm	Cut Out Ø	68 mm
Height	58.5 mm	Control	Dimmable via optional controller
Ø	78 mm	Colour Rendering Index (Ra)	80
Power	8 W		
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		

Article	Housing Color	Colour Temperature	Price
<b>565247</b>	Silver	2400-6500 K	<b>€ 65.95</b>

CV

IP20

A  
↑  
G

E