




### COB 68 RGBW

- Suitable for 24 V colour controls
- swivelling

Housing	Aluminium	Installation Depth	55 mm
Colour Temperature	3000 K	Light Beam Angle	50 Degree
Luminous Flux	500 lm	Swivelling Angle	25 Degree
Height	48 mm	Cut Out Ø	68 mm
Ø	78 mm	Control	Dimmable via optional controller
Power	8.5 W	Colour Rendering Index (Ra)	80
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		

Article	Housing Color		Price
<b>565335</b>	<input type="checkbox"/> White		<b>€ 99.95</b>
<b>565336</b>	<input type="checkbox"/> Silver		<b>€ 99.95</b>



### COB-68-350MA-2700K-SQUARE

Housing	Aluminium	Light Beam Angle	45 Degree
Length	78 mm	Swivelling Angle	25 Degree
Width	78 mm	Cut Out Ø	68 mm
Height	46 mm	Control	Dimmable via optional power supply unit
Power	6 W	Colour Rendering Index (Ra)	90
Rated Input Voltage	16-17 V/DC	Rated Current	350 mA
Power Supply Unit incl.	No		
Installation Depth	50 mm		

Article	Housing Color	Colour Temperature	Luminous Flux	EEL	Price
<b>565282</b>	<input type="checkbox"/> Silver	2700 K	580 lm		<b>€ 59.95</b>
<b>565283</b>	<input type="checkbox"/> White	2700 K	580 lm		<b>€ 59.95</b>
<b>565284</b>	<input type="checkbox"/> Silver	4000 K	660 lm		<b>€ 59.95</b>
<b>565285</b>	<input type="checkbox"/> White	4000 K	660 lm		<b>€ 59.95</b>

