



ACRUX

- Integrated power supply unit
- Light colour adjustable in three levels
- incl. removable ring in silver / black [depending on model]
- Basic housing white, can also be used without colour ring

Housing	Plastic	Control	Leading-edge dimmer, Trailing-edge dimmer
Colour Temperature	3000/4000/6000 K		
Rated Input Voltage	220-240 V/AC		
Power Supply Unit incl.	Yes	Colour Rendering Index (Ra)	80
Light Beam Angle	90 Degree		

Article	Housing Color		Luminous Flux	Ø cut out	Ø	Power	Installation Depth	Price
565315	☐ White, Silver	WW NW CW	630 lm	68 mm	95 mm	7.0 W	55 mm	€ 24.95
565362	▣ White, Black	WW NW CW	630 lm	68 mm	95 mm	7.0 W	55 mm	€ 24.95
565316	☐ White, Silver	WW NW CW	760 lm	90 mm	113 mm	8.0 W	55 mm	€ 29.95
565363	▣ White, Black	WW NW CW	760 lm	90 mm	113 mm	8.0 W	55 mm	€ 29.95
565317	☐ White, Silver	WW NW CW	1370 lm	120 mm	145 mm	14.5 W	63 mm	€ 34.95
565364	▣ White, Black	WW NW CW	1370 lm	120 mm	145 mm	14.5 W	63 mm	€ 34.95
565318	☐ White, Silver	WW NW CW	1570 lm	145 mm	174 mm	16.0 W	63 mm	€ 39.95
565365	▣ White, Black	WW NW CW	1570 lm	145 mm	174 mm	16.0 W	63 mm	€ 39.95
565332	☐ White, Silver	WW NW CW	2670 lm	195 mm	244 mm	26.0 W	82 mm	€ 54.95
565366	▣ White, Black	WW NW CW	2670 lm	195 mm	244 mm	26.0 W	82 mm	€ 54.95

