



UNI II MINI

- „Glow“ effect on the reflector ring
- Can be rotated and swivelled
- Can be individually combined with power supply unit [excl.]

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	3000 K	Swivelling Angle	75 Degree
Luminous Flux	670 lm	Cut Out Ø	95 mm
Height	80 mm	Control	Dimmable via optional power supply unit
Ø	103 mm	Colour Rendering Index (Ra)	90
Power	9 W	Rated Current	500 mA
Rated Input Voltage	18-19 V/DC		
Power Supply Unit incl.	No		
Installation Depth	85 mm		

Article	Housing Color		Price
565342	<input type="checkbox"/> White		€ 99.95
565354	<input checked="" type="checkbox"/> Black		€ 99.95



Accessories

930328	Cover heatsink white for series Uni II Mini		€ 3.55
930329	Cover heatsink black for series Uni II Mini		€ 2.95
930330	Reflector ring white for series Uni II Mini		€ 10.95
930331	Reflector ring black for series Uni II Mini		€ 10.95
930332	Reflector ring gold for series Uni II Mini		€ 10.95
930333	Reflector ring chrome for series Uni II Mini		€ 10.95
930770	Reflector 24° for series Uni II Mini		€ 10.95
930771	Reflector 48° for series Uni II Mini		€ 10.95
180513	BASIC, CC, CC50018/18W		€ 23.95
862236	OCTO, DIM, CC, RSM-12-500T/12W		€ 29.95
862190	BASIC, DIM, Multi CC, IE-12D		€ 59.95