




BASIC

- BEG-eligible, Cost-effective, ready-to-connect solution
- For insertion in grid ceilings
- Installation in surface-mounted and recessed frames possible
- Refurbishment solution for T5/T8 louvre luminaires
- incl. CC power supply unit, 900mAh, 33-38V, 36W

Housing	Aluminium	Light Beam Angle	120 Degree
Height	32 mm	Colour Rendering Index (Ra)	80
Power	30.5 W	IK Protection Class	IK03
Rated Input Voltage	220-240 V/AC	UGR	22
Power Supply Unit incl.	Yes		

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Width	Price
100143	<input type="checkbox"/> White	3000 K	3900 lm	295 mm	1195 mm	€ 79.95
100149	<input type="checkbox"/> White	3000 K	3900 lm	595 mm	595 mm	€ 69.95
100140	<input type="checkbox"/> White	3000 K	3900 lm	620 mm	620 mm	€ 74.95
100144	<input type="checkbox"/> White	4000 K	4320 lm	295 mm	1195 mm	€ 79.95
100150	<input type="checkbox"/> White	4000 K	4320 lm	595 mm	595 mm	€ 69.95
100141	<input type="checkbox"/> White	4000 K	4320 lm	620 mm	620 mm	€ 74.95



Accessories

930674	Safety rope		€ 4.95
930676	Installation bracket for 600x600/300x1200mm Backlit Panel		€ 4.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 69.95

Accessories for **100140, 100141**

930665	Built-up frame for 620x620mm Panel		€ 59.95
930668	Recessed frame for 620x620mm Panel		€ 57.95

Accessories for **100143, 100144**

930666	Built-up frame for 300x1200mm Panel		€ 69.95
930669	Recessed frame for 300x1200mm Panel		€ 67.95

Accessories for **100149, 100150**

930664	Built-up frame for 595x595mm Panel		€ 54.95
930667	Recessed frame for 595x595mm Panel		€ 52.95