




BASIC FLEX





- **BEG-eligible**
- **Light colour adjustable in three stages**
- **For insertion into grid ceilings**
- **Mounting in surface-mounted and recessed frames possible**
- **Refurbishment solution for T5/T8 louvre luminaires**
- **incl. CC power supply unit, 900mAh, 33-38V, 36W**

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	3000/4000/6000 K	Light Beam Angle	120 Degree
Luminous Flux	3900/4320/4140 lm	Colour Rendering Index (Ra)	80
Height	32 mm	IK Protection Class	IK03
Power	30.5 W	UGR	22
Rated Input Voltage	220-240 V/AC		



Article	Housing Color		Length	Width	Price
100145	<input type="checkbox"/> White	ww nw cw	295 mm	1195 mm	€ 99.95
100142	<input type="checkbox"/> White	ww nw cw	620 mm	620 mm	€ 94.95





Accessories

930674	Safety rope		€ 4.95
930676	Installation bracket for 600x600/300x1200mm Backlit Panel		€ 4.95
862264	BASIC, DIM, CC, D090040NTF/40W		€ 46.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 69.95

Accessories for 100142

930665	Built-up frame for 620x620mm Panel		€ 59.95
930668	Recessed frame for 620x620mm Panel		€ 57.95

Accessories for 100145

930666	Built-up frame for 300x1200mm Panel		€ 69.95
930669	Recessed frame for 300x1200mm Panel		€ 67.95