




## BASIC OFFICE

- For insertion in grid ceilings
- Mounting in surface-mounted and recessed frames possible
- Suitable for screen workstations in accordance with EN 12464-1 BAP65
- Microprismatic surface structure
- Suitable for offices, lounges and walkways
- Cost-effective ready-to-connect solution
- incl. power supply unit CC, 900mAh, 33-38V, 36W

Housing	Aluminium	Power Supply Unit incl.	Yes
Colour Temperature	4000 K	Light Beam Angle	90 Degree
Luminous Flux	4000 lm	Colour Rendering Index (Ra)	80
Height	32 mm	IK Protection Class	IK03
Power	30.5 W	UGR	19
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Length	Width	Price
100147	<input type="checkbox"/> White	295 mm	1195 mm	€ 89.95
100151	<input type="checkbox"/> White	595 mm	595 mm	€ 79.95
100146	<input type="checkbox"/> White	620 mm	620 mm	€ 84.95



### Accessories

<b>930674</b>	Safety rope		€ 4.95
<b>930676</b>	Installation bracket for 600x600/300x1200mm Backlit Panel		€ 4.95
<b>862264</b>	BASIC, DIM, CC, D090040NTF/40W		€ 46.95
<b>862192</b>	BASIC, DIM, Multi CC, IE-45D		€ 69.95

### Accessories for 100146

<b>930665</b>	Built-up frame for 620x620mm Panel		€ 59.95
<b>930668</b>	Recessed frame for 620x620mm Panel		€ 57.95

### Accessories for 100147

<b>930666</b>	Built-up frame for 300x1200mm Panel		€ 69.95
<b>930669</b>	Recessed frame for 300x1200mm Panel		€ 67.95

### Accessories for 100151

<b>930664</b>	Built-up frame for 595x595mm Panel		€ 54.95
<b>930667</b>	Recessed frame for 595x595mm Panel		€ 52.95