



PRO OFFICE

- BEG-eligible
- for insertion in grid ceilings
- Installation in surface-mounted and recessed frames possible
- Highly efficient solution
- refurbishment solution for T5 / T8 louvre luminaires
- Suitable for offices / recreation rooms / path areas
- suitable for VDU workstations in accordance with EN 12464-1 BAP65
- Microprismatic surface structure
- can be individually combined with power supply unit [excl.]

Housing	Aluminium	Control	Dimmable via optional power supply unit
Height	32 mm		
Power	17 W		
Rated Input Voltage	35-40 V/DC	Colour Rendering Index (Ra)	80
Power Supply Unit incl.	No	Rated Current	450 mA
Light Beam Angle	90 Degree	IK Protection Class	IK03
		UGR	19

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Width	EEL	Price
100084	<input type="checkbox"/> White	3000 K	2880 lm	620 mm	620 mm		€ 109.95
100089	<input type="checkbox"/> White	3000 K	2880 lm	1195 mm	295 mm		€ 114.95
100122	<input type="checkbox"/> White	4000 K	3200 lm	1195 mm	295 mm		€ 114.95
100148	<input type="checkbox"/> White	4000 K	3200 lm	595 mm	595 mm		€ 104.95
100088	<input type="checkbox"/> White	4000 K	3200 lm	620 mm	620 mm		€ 109.95

