



STANDARD FLEX

- Light colour adjustable in three levels
- For insertion into grid ceilings
- Mounting in surface-mounted and recessed frames possible
- Suspension possible
- Suitable for lounges and path areas
- Can be individually combined with power supply unit [excl.]

Housing	Aluminium	Control	Dimmable via optional power supply unit
Colour Temperature	3000/4000/6000 K		
Height	10 mm		
Rated Input Voltage	33-38 V/DC	Colour Rendering Index (Ra)	90
Power Supply Unit incl.	No	IK Protection Class	IK03
Light Beam Angle	120 Degree	UGR	22

Article	Housing Color		Luminous Flux	Length	Width	Power	Rated Current	Price
100125	<input type="checkbox"/> White	WW NW CW	3570/3990/3780 lm	1195 mm	295 mm	36.0 W	1050 mA	€ 124.95
100123	<input type="checkbox"/> White	WW NW CW	3780/4200/4000 lm	620 mm	620 mm	36.0 W	1050 mA	€ 119.95
100139	<input type="checkbox"/> White	WW NW CW	5300/6000/5700 lm	1195 mm	595 mm	51.5 W	1500 mA	€ 219.95
100154	<input type="checkbox"/> White	WW NW CW	5300/6000/5700 lm	1240 mm	620 mm	51.5 W	1500 mA	€ 229.95

