



STANDARD OFFICE

- For insertion into grid ceilings
- Mounting in surface-mounted and recessed frames possible
- Suspension possible
- Suitable for offices, lounges, path areas
- suitable for screen workstations in accordance with EN 12464-1 BAP65
- microprismatic surface structure

Housing	Aluminium	Control	Dimmable via optional power supply unit
Colour Temperature	4000 K		
Luminous Flux	4200 lm	Colour Rendering Index (Ra)	90
Height	9 mm	Rated Current	1050 mA
Power	36 W	IK Protection Class	IK03
Rated Input Voltage	33-38 V/DC	UGR	19
Power Supply Unit incl.	No		
Light Beam Angle	90 Degree		

Article	Housing Color	Length	Width	EEL	Price
100138	<input type="checkbox"/> White	295 mm	1195 mm		€ 129.95
100124	<input type="checkbox"/> White	620 mm	620 mm		€ 124.95



Accessories

930672	Rope suspension for 620x620/300x1200mm Panel		€ 22.95
930674	Safety rope		€ 4.95
862258	QUICK, CC, 1,050 mA, 25-40 V, 45 W		€ 46.95
862193	BASIC, DIM, Multi CC, IE-45HD		€ 69.95

Accessories for 100124

930665	Built-up frame for 620x620mm Panel		€ 59.95
930670	Recessed frame for 620x620mm Backlit Panel		€ 59.95

Accessories for 100138

930666	Built-up frame for 300x1200mm Panel		€ 69.95
930671	Recessed frame for 300x1200mm Backlit Panel		€ 69.95