



OFFICE FLEX

- For insertion into grid ceilings
- Mounting in surface-mounted and recessed frames possible
- Suspension possible
- Suitable for offices, lounges, path areas
- Light colour adjustable in three stages
- suitable for VDU workstations in accordance with EN 12464-1 BAP65
- microprismatic surface structure

Housing	Aluminium	Control	Leading-edge dimmer, Trailing-edge dimmer
Colour Temperature	3000/4000/5700 K	Colour Rendering Index (Ra)	90
Height	10 mm	IK Protection Class	IK08
Power	40 W	UGR	19
Rated Input Voltage	220-240 V/AC		
Power Supply Unit incl.	Yes		
Light Beam Angle	100 Degree		

Article	Housing Color		Luminous Flux	Length	Width	Price
100078	<input type="checkbox"/> White	<input type="checkbox"/> WW <input type="checkbox"/> NW <input type="checkbox"/> CW	3300 lm	620 mm	620 mm	€ 179.95
100079	<input type="checkbox"/> White	<input type="checkbox"/> WW <input type="checkbox"/> NW <input type="checkbox"/> CW	3500 lm	1195 mm	295 mm	€ 219.95



Accessories

862193 BASIC, DIM, Multi CC, IE-45HD  **€ 69.95**

Accessories for 100078

930665 Built-up frame for 620x620mm Panel  **€ 59.95**

930670 Recessed frame for 620x620mm Backlit Panel  **€ 59.95**

Accessories for 100079

930666 Built-up frame for 300x1200mm Panel  **€ 69.95**

930671 Recessed frame for 300x1200mm Backlit Panel  **€ 69.95**