




## HCL






- For insertion in grid ceilings
- Installation in surface-mounted and recessed frames possible
- Suitable for 24 V HCL control units
- Suitable for event rooms / recreation rooms, path areas
- low housing depth

Housing	Aluminium	Rated Input Voltage	24 V/DC
Colour Temperature	3000-5500 K	Power Supply Unit incl.	No
Luminous Flux	3551 lm	Light Beam Angle	120 Degree
Length	620 mm	Control	Dimmable via optional controller
Width	620 mm	Colour Rendering Index (Ra)	80
Height	10 mm		
Power	49.5 W		

Article	Housing Color	Colour Temperature	Price
<b>100032</b>	<input type="checkbox"/> White	<input checked="" type="checkbox"/> WW <input checked="" type="checkbox"/> CW 3000-5500 K	<b>€ 159.95</b>



### Accessories

<b>930665</b>	Built-up frame for 620x620mm Panel		<b>€ 59.95</b>
<b>930670</b>	Recessed frame for 620x620mm Backlit Panel		<b>€ 59.95</b>
<b>862122</b>	FLAT, CV, UT24V/50W		<b>€ 52.95</b>
<b>862166</b>	BASIC, CV, Q8H-24-100W		<b>€ 96.95</b>
<b>843501</b>	RF-smart, Starter-Set LED Single/CCT, 12-48V, 20A remote control incl.		<b>€ 99.95</b>