




STANDARD RGBW

- For insertion in grid ceilings
- Installation in surface-mounted and recessed frames possible
- Powerful and intense colours including pastel shades
- Suitable for 24 V colour controls
- suitable for event rooms, recreation rooms, path areas

Housing	Aluminium	Light Beam Angle	110 Degree
Height	11 mm	Control	Dimmable via optional controller
Power	94 W	Colour Rendering Index (Ra)	90
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Width	Price
100156	<input type="checkbox"/> White	3000 K	4000 lm	595 mm	595 mm	€ 184.95
100152	<input type="checkbox"/> White	3000 K	4000 lm	620 mm	620 mm	€ 189.95
100157	<input type="checkbox"/> White	4000 K	4200 lm	595 mm	595 mm	€ 184.95
100153	<input type="checkbox"/> White	4000 K	4200 lm	620 mm	620 mm	€ 189.95



Accessories

862166	BASIC, CV, Q8H-24-100W		€ 96.95
872091	IP, CV, V6-320-24		€ 219.95
843502	RF-smart, Starter-Set RGB/W/CCT, 12-48V, 20A remote control, IP20 incl.		€ 99.95
843037	Bluetooth controller CBU-PWM4		€ 179.95
843279	MULTI-LED-Dimmer 1-4 CH, DMX/AUTO/MAN, 12-48V, 20A		€ 114.95

Accessories for 100152, 100153

930665	Built-up frame for 620x620mm Panel		€ 59.95
930668	Recessed frame for 620x620mm Panel		€ 57.95

Accessories for 100156, 100157

930664	Built-up frame for 595x595mm Panel		€ 54.95
930667	Recessed frame for 595x595mm Panel		€ 52.95