



HERCULIS SINGLE

- High performance with compact design
- Rotating and swivelling head
- for recessed and surface mounting thanks to intelligent cable routing
- Ready-to-plug-in system
- Available in two sizes

| | | | |
|---------------------|-----------|-----------------------------|------------|
| Housing | Aluminium | Rated Current | 350 mA |
| Luminous Flux | 100 lm | Power Supply Unit incl. | No |
| Ø | 39.2 mm | Light Beam Angle | 30 Degree |
| Base Height | 4.5 mm | Swivelling Angle | 350 Degree |
| Base Ø | 39.2 mm | Colour Rendering Index (Ra) | 90 |
| Power | 1 W | | |
| Rated Input Voltage | 3 V/DC | | |

| Article | Housing Color | Colour Temperature | Height | Price |
|---------------|---------------|--------------------|--------|---------|
| 688029 | Black | 3000 K | 150 mm | € 79.95 |
| 688030 | Silver | 3000 K | 150 mm | € 79.95 |
| 688034 | Black | 3000 K | 250 mm | € 79.95 |
| 688035 | Silver | 3000 K | 250 mm | € 79.95 |
| 688031 | Black | 4000 K | 150 mm | € 79.95 |
| 688033 | Silver | 4000 K | 150 mm | € 79.95 |
| 688036 | Black | 4000 K | 250 mm | € 79.95 |
| 688037 | Silver | 4000 K | 250 mm | € 79.95 |



Accessories

- 930594** LED-power supply incl. 3 times distributor for Herculis
- 930592** LED-power supply incl. 6 times distributor for Herculis



€ 32.95

€ 39.95