



LED PANEL TRANSPARENT ROUND

·Very low glare value

·Transparent luminous element

Housing	Aluminium	Power Supply Unit incl.	Yes
Rated Input Voltage	220-240 V/AC	Light Beam Angle	150 Degree
Height	12.5 mm	Control	Leading-edge dimmer, Trailing-edge dimmer
Ø	580 mm	Colour Rendering Index (Ra)	80
Pendulum Length	1500 mm		
Base Ø	250 mm		
Base Height	45 mm		

Article	Housing Color	Colour Temperature	Luminous Flux	Power	Price
342089	■ Black	ww 3000 K	6612 lm	53.3 W	€ 379.95
342090	□ Aluminum	ww 3000 K	6612 lm	53.3 W	€ 379.95
342091	□ White	ww 3000 K	6612 lm	53.3 W	€ 379.95
342092	■ Black	nw 4000 K	6776 lm	53.7 W	€ 379.95
342093	□ Aluminum	nw 4000 K	6776 lm	53.7 W	€ 379.95
342094	□ White	nw 4000 K	6776 lm	53.7 W	€ 379.95



Accessories

843340 DALI, Triac-Dimmer, 100-240V, 400W, IP20



€ 74.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.