









### TRI PROOF BASIC DALI

- Eligible for German BEG federal funding
- Can run on emergency power (180-264 V/DC EOFI: 15%)
- particularly energy efficient
- long service life of 50,000 hours L80B50
- Pre-installed feed-through wiring 3x1.5 mm<sup>2</sup>/5x1.5 mm<sup>2</sup> (DALI)
- cable entry point on the back
- Stainless steel clips on the cover can be locked with screws
- robust plastic housing

Housing	Polycarbonate (PC)/ iron	Power Supply Unit incl.	Yes
Colour Temperature	4000 K	Control	DALI 2 / DT6, Push-Dim
Width	82 mm	Colour Rendering Index (Ra)	80
Height	75 mm	IK Protection Class	IK08
Rated Input Voltage	220-240 V/AC		
Number in Row max.	15		

Article	Housing Color	Luminous Flux	Length	Power	Price
<b>730485</b>	Grey  	2520 lm	610 mm	18.0 W	<b>€ 104.95</b>
<b>730488</b>	Grey  	5040 lm	1210 mm	36.0 W	<b>€ 129.95</b>
<b>730491</b>	Grey  	7700 lm	1510 mm	55.0 W	<b>€ 159.95</b>



Accessories

**930713** Rope suspension for Tri Proof Basic



**€ 19.95**