







TRI PROOF

- Pre-installed feed-through wiring
- Including mounting clips

Housing	Plastic	Power Supply Unit incl.	Yes
Surface	Matt	Light Beam Angle	120 Degree
Colour Temperature	4000 K	Colour Rendering Index (Ra)	80
Width	61 mm	IK Protection Class	IK08
Height	56 mm		
Rated Input Voltage	180-240 V/AC		



Article	Housing Color	Luminous Flux	Length	Power	Number in Row max.	Price
730419	<input type="checkbox"/> White 	1430 lm	696 mm	17.0 W	25	€ 49.95
730424	<input type="checkbox"/> White 	2980 lm	1296 mm	35.0 W	15	€ 79.95
730425	<input type="checkbox"/> White 	3820 lm	1598 mm	44.0 W	10	€ 84.95



TRI PROOF MOTION

- including mounting clips

Housing	Plastic	Power Supply Unit incl.	Yes
Surface	Matt	Light Beam Angle	120 Degree
Colour Temperature	4000 K	Colour Rendering Index (Ra)	80
Width	61 mm	IK Protection Class	IK08
Height	56 mm		
Rated Input Voltage	220-240 V/AC		

Article	Housing Color	Luminous Flux	Length	Power	Price
730450	<input type="checkbox"/> White 	1900 lm	665 mm	18.5 W	€ 59.95
730455	<input type="checkbox"/> White 	2500 lm	1145 mm	24.5 W	€ 74.95



Accessories

930071 Rope suspension adjustable for Tri Proof Set 2 pcs



€ 14.95

930072 Surface mounting bracket for Tri Proof 2 pcs



€ 14.95