



## D LINE THREE-PHASE ADAPTER WITH INTEGRATED MULTI CC POWER SUPPLY

- Suitable for surface-mounted and recessed systems
- Integrated secondary fall protection
- Supplied with trumpet nipple and M10 flat nut
- integrated, adjustable, current-stable power supply unit [CC]
- Check suitability of the intended luminaire
- max. 10kg / 100N
- exclusively for 3-phase track from D LINE, Ivela, Hoffmeister

Housing	Plastic	Height	41 mm
Length	162 mm	Rated Input Voltage	220-240 V/AC
Width	31 mm	Mounting Location	Inside

Article		Output Current Selectable	Power	Output Voltage	Price
<b>862180</b>	<input type="checkbox"/>	250 mA / 350 mA / 450 mA / 500 mA	6.2-21.0 W	25-42 V/DC	<b>€ 32.95</b>
<b>862183</b>	<input checked="" type="checkbox"/>	250 mA / 350 mA / 450 mA / 500 mA	6.2-21.0 W	25-42 V/DC	<b>€ 32.95</b>
<b>862181</b>	<input type="checkbox"/>	600 mA / 700 mA / 750 mA / 800 mA	15.0-33.0 W	25-42 V/DC	<b>€ 35.95</b>
<b>862184</b>	<input checked="" type="checkbox"/>	600 mA / 700 mA / 750 mA / 800 mA	15.0-33.0 W	25-42 V/DC	<b>€ 35.95</b>
<b>862182</b>	<input type="checkbox"/>	850 mA / 900 mA / 950 mA / 1050 mA	22.0-44.0 W	27-42 V/DC	<b>€ 37.95</b>
<b>862185</b>	<input checked="" type="checkbox"/>	850 mA / 900 mA / 950 mA / 1050 mA	22.0-44.0 W	27-42 V/DC	<b>€ 37.95</b>

