




ALNITAK

- Power adjustable in four stages
- can be rotated and swivelled
- low glare value
- for D LINE, Ivela and Hoffmeister three-phase current tracks

Housing	Aluminium	Rated Input Voltage	220-240 V/AC
Length	336 mm	Power Supply Unit incl.	Yes
Width	36 mm	Light Beam Angle	34 Degree
Height	49 mm	Swivelling Angle	25 Degree
Power Selectable	25.2 W, 29.4 W, 31.5 W, 33.6 W	Colour Rendering Index (Ra)	80

Article	Housing Color	Colour Temperature	Luminous Flux	Price
707110	<input type="checkbox"/> White	<input checked="" type="checkbox"/> WW 3000 K	3114 lm	€ 169.95
707112	<input checked="" type="checkbox"/> Silver	<input checked="" type="checkbox"/> WW 3000 K	3114 lm	€ 169.95
707114	<input checked="" type="checkbox"/> Black	<input checked="" type="checkbox"/> WW 3000 K	3114 lm	€ 169.95
707111	<input type="checkbox"/> White	<input checked="" type="checkbox"/> NW 4000 K	3068 lm	€ 169.95
707113	<input checked="" type="checkbox"/> Silver	<input checked="" type="checkbox"/> NW 4000 K	3068 lm	€ 169.95
707115	<input checked="" type="checkbox"/> Black	<input checked="" type="checkbox"/> NW 4000 K	3068 lm	€ 169.95



Accessories

930386	Reflector for Ain, Alnitak 12°		€ 1.95
930387	Reflector for Ain, Alnitak 48°		€ 1.95
930388	Ceti Spot anti glare white		€ 2.95