



LINEAR PRO TILT

- Eligible for German BEG federal funding
- can run on emergency power [198-264 V/DC EOFI: 100%]
- can be locked shining downwards
- can be swivelled up to 30° to each side
- long service life of 60,000 hours (L80B50)
- particularly energy efficient
- Output adjustable in three steps

Housing	Steel	Light Beam Angle	60 Degree
Width	60 mm	Swivelling Angle	60 Degree
Height	54 mm	Colour Rendering Index (Ra)	90
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK03
Power Supply Unit incl.	Yes		

Article	Housing Color	Colour Temperature	Luminous Flux	Length	Power Selectable	Price
707195	<input type="checkbox"/> White	3000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 149.95
707196	<input checked="" type="checkbox"/> Black	3000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 149.95
707197	<input type="checkbox"/> White	3000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 184.95
707198	<input checked="" type="checkbox"/> Black	3000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 184.95
707141	<input type="checkbox"/> White	4000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 149.95
707142	<input checked="" type="checkbox"/> Black	4000 K	3200 lm	600 mm	14.0 W / 16.0 W / 18.0 W / 20.0 W	€ 149.95
707143	<input type="checkbox"/> White	4000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 184.95
707144	<input checked="" type="checkbox"/> Black	4000 K	8000 lm	1493 mm	35.0 W / 40.0 W / 45.0 W / 50.0 W	€ 184.95

