



HORUS

- low glare value
- can be rotated and swivelled

Housing	Plastic	Light Beam Angle	40 Degree
Surface	Matt	Swivelling Angle	350 Degree
Rated Input Voltage	220-240 V/AC	Colour Rendering Index (Ra)	80
Power Supply Unit incl.	Yes		

Article	Housing Color	Colour Temperature	Luminous Flux	Height	Ø	Power	EEL	Price
707094	Black	3000 K	625 lm	125 mm	60 mm	7.0 W	E	€ 69.95
707095	White	3000 K	625 lm	125 mm	60 mm	7.0 W	E	€ 69.95
707098	Black	3000 K	915 lm	140 mm	70 mm	10.0 W	E	€ 79.95
707099	White	3000 K	915 lm	140 mm	70 mm	10.0 W	E	€ 79.95
707102	Black	3000 K	1705 lm	185 mm	80 mm	20.0 W	F	€ 89.95
707103	White	3000 K	1705 lm	185 mm	80 mm	20.0 W	F	€ 89.95
707106	Black	3000 K	2525 lm	210 mm	90 mm	30.0 W	F	€ 109.95
707107	White	3000 K	2525 lm	210 mm	90 mm	30.0 W	F	€ 109.95
707096	Black	4000 K	635 lm	125 mm	60 mm	7.0 W	E	€ 69.95
707097	White	4000 K	635 lm	125 mm	60 mm	7.0 W	E	€ 69.95
707100	Black	4000 K	1030 lm	140 mm	70 mm	10.0 W	E	€ 79.95
707101	White	4000 K	1030 lm	140 mm	70 mm	10.0 W	E	€ 79.95
707104	Black	4000 K	1785 lm	185 mm	80 mm	20.0 W	F	€ 89.95
707105	White	4000 K	1785 lm	185 mm	80 mm	20.0 W	F	€ 89.95
707108	Black	4000 K	2605 lm	210 mm	90 mm	30.0 W	F	€ 109.95
707109	White	4000 K	2605 lm	210 mm	90 mm	30.0 W	F	€ 109.95

