



## FARO

- Glare-free, light directed downwards (>97 %)
- Lens optics for wide homogeneous illumination with up to 4/7/10 m diameter
- Optional screening shade for darkening on one side
- IP68 connection box with feed-through wiring
- Particularly high-quality and solid construction
- Dirt-repellent powder coating in DB703
- Emergency power capable (180-264V/DC EOFI: 100%)

Housing	Aluminium	Light Beam Angle	360 Degree
Colour Temperature	3000 K	Light Beam Angle 2	180 Degree
Luminous Flux	1030 lm	Control	DALI 2 / DT6
Ø	180 mm	Colour Rendering Index (Ra)	80
Power	24 W	IK Protection Class	IK10
Rated Input Voltage	180-264V/AC		
Power Supply Unit incl.	Yes		

Article	Housing Color		Height	Price
<b>730492</b>	Grey		250 mm	<b>€ 429.95</b>
<b>730493</b>	Grey		600 mm	<b>€ 499.95</b>
<b>730494</b>	Grey		1000 mm	<b>€ 579.95</b>



### Accessories

- 930731** Concrete anchor for series Faro **€ 24.95**
- 930776** Shield cover 180 degree for series Faro **€ 9.95**



### Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.