




### FLAT 24V

Housing	Stainless steel, Aluminium	Installation Depth	50 mm
Luminous Flux	510 lm	Light Beam Angle	30 Degree
Height	38 mm	Cut Out Ø	150 mm
Ø	173 mm	Control	Dimmable via optional controller
Power	17 W	Primary Cable Length	0.5 m
Rated Input Voltage	24 V/DC	Primary Connection End	WEIPU plug 4-pole
Power Supply Unit incl.	No	Light Distribution	Symmetric

Article	Housing Color	Price
<b>100116</b>	Silver	<b>€ 309.95</b>



Accessories

<b>872083</b>	IP, CV, V6-40-24		<b>€ 74.95</b>
<b>843502</b>	RF-smart, Starter-Set RGB/W/CCT, 12-48V, 20A remote control, IP20 incl.		<b>€ 99.95</b>



### FLAT 230V 20 DEGREE

·Including 0.5 m connecting cable

Housing	Stainless steel, Aluminium	Colour Rendering Index (Ra)	80
Colour Temperature	3000 K	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
Power Supply Unit incl.	Yes	Light Distribution	Symmetric
Light Beam Angle	20 Degree		

Article	Housing Color	Luminous Flux	Ø cut out	Height	Ø	Power	Installation Depth	Price
<b>100111</b>	Silver	400 lm	105 mm	44 mm	116 mm	5.8 W	44 mm	<b>€ 189.95</b>
<b>100114</b>	Silver	860 lm	150 mm	42 mm	173 mm	12.2 W	42 mm	<b>€ 269.95</b>

