



### CANUM 230V SYMMETRICAL

·Including connecting cable

Housing	Stainless steel, Aluminium	Installation Depth	150 mm
Colour Temperature	3000 K	Light Beam Angle	30 Degree
Luminous Flux	280 lm	Cut Out Ø	102 mm
Height	102 mm	Colour Rendering Index (Ra)	80
Ø	116 mm	Primary Cable Length	0.5 m
Power	4.1 W	Primary Connection End	Connection box
Rated Input Voltage	220-240 V/AC	Light Distribution	Symmetric
Power Supply Unit incl.	Yes		

Article      Housing Color      Price

**730255**    Silver           **€ 179.95**



### CANUM 230V ASYMMETRICAL

·Asymmetrical

·Including 0.5 m connecting cable

Housing	Stainless steel, Aluminium	Light Beam Angle	45 Degree
Colour Temperature	3000 K	Light Beam Angle 2	35 Degree
Luminous Flux	700 lm	Cut Out Ø	157 mm
Height	111 mm	Colour Rendering Index (Ra)	80
Ø	173 mm	Primary Cable Length	0.5 m
Power	11.9 W	Primary Connection End	Connection box
Rated Input Voltage	220-240 V/AC	IK Protection Class	IK09
Power Supply Unit incl.	Yes	Light Distribution	Asymmetric
Installation Depth	153 mm		

Article      Housing Color      Price

**730289**    Silver           **€ 259.95**

