



## SQUARE BEAM

·Including 0.5 m connecting cable

Housing	Stainless steel, Aluminium	Installation Depth	95 mm
Colour Temperature	3000 K	Light Beam Angle	25 Degree
Luminous Flux	700 lm	Cut Out Length	112 mm
Length	125 mm	Cut Out Width	112 mm
Width	125 mm	Colour Rendering Index (Ra)	80
Height	75 mm	Primary Cable Length	0.5 m
Power	7.7 W	Primary Connection End	Connection box
Rated Input Voltage	220-240 V/AC	Light Distribution	Symmetric
Power Supply Unit incl.	Yes		

Article      Housing Color      Price

**730209**    Silver            **€ 169.95**



## SQUARE SOFT

Housing	Stainless steel, Aluminium	Installation Depth	95 mm
Colour Temperature	3000 K	Light Beam Angle	120 Degree
Luminous Flux	160 lm	Cut Out Length	113.5 mm
Length	125 mm	Cut Out Width	113.5 mm
Width	125 mm	Colour Rendering Index (Ra)	80
Height	75 mm	Primary Cable Length	0.5 m
Power	3.2 W	Primary Connection End	Connection box
Rated Input Voltage	220-240 V/AC	Light Distribution	Symmetric
Power Supply Unit incl.	Yes		

Article      Housing Color      Price

**730248**    Silver            **€ 179.95**

