



LINE

•Including connecting cable

Housing	Stainless steel, Aluminium	Light Beam Angle	20 Degree
Colour Temperature	3000 K	Cut Out Width	68 mm
Width	68 mm	Colour Rendering Index (Ra)	80
Height	31.5 mm	Primary Cable Length	0.5 m
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
Power Supply Unit incl.	Yes	IK Protection Class	IK07
Installation Depth	80 mm	Light Distribution	Symmetric

Article	Housing Color		Luminous Flux	Length	Power	Cut Out Length	Price
730434	Silver	WW	1100 lm	549 mm	18.0 W	527 mm	€ 379.95
730432	Silver	WW	2300 lm	1025 mm	36.0 W	1007 mm	€ 599.95



LINE ASYMMETRICAL

Housing	Stainless steel, Aluminium	Light Beam Angle	45 Degree
Colour Temperature	3000 K	Light Beam Angle 2	35 Degree
Width	63 mm	Cut Out Width	58 mm
Height	65 mm	Colour Rendering Index (Ra)	80
Rated Input Voltage	220-240 V/AC	Primary Connection End	Connection box
Power Supply Unit incl.	Yes	Light Distribution	Asymetric
Installation Depth	90 mm		

Article	Housing Color		Luminous Flux	Length	Power	Cut Out Length	Primary Cable Length	Price
730292	Silver	WW	340 lm	195 mm	5.5 W	180 mm	0.5 m	€ 179.95
730262	Silver	WW	730 lm	328 mm	11.9 W	313 mm	1 m	€ 249.95

