



FLOOD SMD

- Including 1.2 m connecting cable with IP44 shaped plug
- Housing made of durable die-cast aluminium and glass

Housing	Aluminium	Primary Connection End	Power plug IP44
Rated Input Voltage	220-240 V/AC	Colour Rendering Index (Ra)	80
Power Supply Unit incl.	Yes	IP Protection Type Plug	IP 44
Light Beam Angle	100 Degree	IK Protection Class	IK08
Primary Cable Length	1.2 m		

Article	Housing Color	Colour Temp.	Luminous Flux	Length	Width	Height	power	EEL	Price
732147	Silver	3000 K	1800 lm	179 mm	143.6 mm	27 mm	15 W	E	€ 89.95
732148	Black	3000 K	1800 lm	179 mm	143.6 mm	27 mm	15 W	E	€ 89.95
732150	Silver	3000 K	3600 lm	237 mm	250 mm	40.5 mm	30 W	E	€ 129.95
732151	Black	3000 K	3600 lm	237 mm	250 mm	40.5 mm	30 W	E	€ 129.95
732149	Silver	4000 K	1950 lm	179 mm	143.6 mm	27 mm	15 W	E	€ 89.95
732152	Silver	4000 K	3900 lm	237 mm	250 mm	40.5 mm	30 W	D	€ 129.95



page 351

page 351



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.