



ATIK

- IEC62662 - Protection against mechanical effects (IK Code)
- EN60598-2-24 - Lights for use in explosive gas and dust atmosphere (D designation)
- Including 2 m connecting cable with IP44 plug

Housing	Aluminium	Swivelling Angle	180 Degree
Colour Temperature	4000 K	Primary Cable Length	2 m
Length	319 mm	Primary Connection End	Power plug IP44
Width	90 mm	Colour Rendering Index (Ra)	80
Height	411 mm	IP Protection Type Plug	IP 44
Power Supply Unit incl.	Yes	IK Protection Class	IK08
Light Beam Angle	110 Degree		

Article	Housing Color		Luminous Flux	Power	Rated Input Voltage	EEL	Price
732096	Black	NW	21350 lm	152.0 W	220-240 V/AC	D	€ 419.95
732097	Black	NW	28450 lm	202.0 W	220-240 V/AC	D	€ 529.95
732098	Black	NW	31800 lm	242.0 W	220-240 V/AC	D	€ 599.95
732102	Black	NW	39900 lm	302.0 W	100-240 V/AC	E	€ 699.95



Onlineshop

You can find more information about the products in the onlineshop: Detailed images, videos, project reports, LDT files, EPREL data sheets and more.