



DEKO-LIGHT POWER SUPPLY UNITS CV | BASIC DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection

Housing Plastic Mounting Location Inside
 Rated Input Voltage 220-240 V/AC

Article	Output Voltage	Power	Output Current	Length	Width	Height	Price
862162 ■	12 V/DC	40.0 W	0-3300 mA	166 mm	52 mm	24 mm	€ 46.95
862127 ■	12 V/DC	75.0 W	0-6300 mA	184 mm	61 mm	32 mm	€ 74.95
862165 ■	12 V/DC	100.0 W	0-8300 mA	184 mm	61 mm	32 mm	€ 96.95
862167 ■	12 V/DC	150.0 W	0-12500 mA	210 mm	67 mm	34 mm	€ 129.95
862163 ■	24 V/DC	40.0 W	0-1700 mA	166 mm	52 mm	24 mm	€ 46.95
862164 ■	24 V/DC	75.0 W	0-3100 mA	184 mm	61 mm	32 mm	€ 74.95
862166 ■	24 V/DC	100.0 W	0-4200 mA	184 mm	61 mm	32 mm	€ 96.95
862168 ■	24 V/DC	150.0 W	0-6250 mA	210 mm	67 mm	34 mm	€ 129.95



Technical data sheet

New in the onlineshop: The technical data sheets offer even more information: Light and energy data, light distribution curves, dimensional drawings and more.