



## DEKO-LIGHT POWER SUPPLY UNITS CV DIM | BASIC DESIGN

- Dimmable with leading edge/trailing edge phase dimmers
- Ideal for retrofitting existing installations, as primarily dimmable with rotary/switch dimmers dimmers (C-compatible)
- cannot be combined with PWM dimmers such as RF, DMX, DALI, KNX
- Flicker-free
- Short-circuit and overload-proof
- overheating protection

Housing	Plastic	Channels	1
Rated Input Voltage	220-240 V/AC	Mounting Location	Inside

Article	Output Voltage	Power	Length	Width	Height	Price
<b>862240</b> ■	12 V/DC	2.5-25.0 W	122 mm	52 mm	30 mm	<b>€ 54.95</b>
<b>862220</b> ■	12 V/DC	12.0-50.0 W	184 mm	61 mm	33 mm	<b>€ 74.95</b>
<b>862241</b> ■	12 V/DC	34.0-100.0 W	210 mm	67 mm	34 mm	<b>€ 144.95</b>
<b>862221</b> ■	24 V/DC	2.5-25.0 W	122 mm	52 mm	30 mm	<b>€ 54.95</b>
<b>862222</b> ■	24 V/DC	12.0-50.0 W	184 mm	61 mm	33 mm	<b>€ 74.95</b>
<b>862242</b> ■	24 V/DC	34.0-100.0 W	210 mm	67 mm	34 mm	<b>€ 144.95</b>
<b>862274</b> ■	48 V/DC	34.0-100.0 W	210 mm	67 mm	34 mm	<b>€ 144.95</b>

