



MEANWELL POWER SUPPLY UNITS CV DIM IP | ELG/HLG SERIES

- can be dimmed using 0-10 V/1-10 V
- flicker-free, secured against short circuits and overloads
- Overheating protection

Housing	Aluminium	Height	48.5 mm
Output Voltage	48 V/DC	Rated Input Voltage	90-305 V/AC
Power	600 W	Channels	1
Length	280 mm	Mounting Location	Inside, Outside
Width	144 mm		

Article Price

872126 **€ 499.95**



MEANWELL POWER SUPPLY UNITS CV DIM | PWM KNX

- can be dimmed using KNX bus
- flicker-free, secured against short circuits and overloads
- Overheating protection

Housing	Plastic	Channels	1
Rated Input Voltage	90-305 V/AC	Mounting Location	Inside

Article	Output Voltage	Power	Length	Width	Height	Price
872109	12 V/DC	60.0 W	150 mm	53 mm	35 mm	€ 159.95
872110	12 V/DC	120.0 W	191 mm	63 mm	37.5 mm	€ 209.95
872111	12 V/DC	200.0 W	195 mm	68 mm	39.5 mm	€ 244.95
872112	24 V/DC	60.0 W	150 mm	53 mm	35 mm	€ 159.95
872113	24 V/DC	120.0 W	191 mm	63 mm	37.5 mm	€ 209.95
872114	24 V/DC	200.0 W	195 mm	68 mm	39.5 mm	€ 244.95
872115	48 V/DC	200.0 W	195 mm	68 mm	39.5 mm	€ 244.95

