



## DEKO-LIGHT POWER SUPPLY UNITS CC | BASIC DESIGN

- Flicker-free
- Secured against short circuits and overloads
- Overheating protection

Housing Plastic Mounting Location Inside  
 Rated Input Voltage 220-240 V/AC

Article	Output Current	Power	Output Voltage	Length	Width	Height	Price
<b>180512</b>	350 mA	0.7-18.0 W	2-52 V/DC	115 mm	45 mm	21 mm	€ 23.95
<b>180513</b>	500 mA	1.0-18.0 W	2-38 V/DC	115 mm	45 mm	21 mm	€ 23.95
<b>862196</b>	500 mA	15.0-30.0 W	30-60 V/DC	127 mm	43 mm	28 mm	€ 26.95
<b>862197</b>	500 mA	20.0-40.0 W	40-80 V/DC	127 mm	43 mm	28 mm	€ 29.95
<b>180514</b>	700 mA	1.4-18.0 W	2-26 V/DC	115 mm	45 mm	21 mm	€ 23.95
<b>862198</b>	700 mA	14.0-30.0 W	21-43 V/DC	127 mm	43 mm	28 mm	€ 26.95
<b>862199</b>	700 mA	20.0-40.0 W	29-57 V/DC	127 mm	43 mm	28 mm	€ 29.95
<b>862157</b>	900 mA	19.0-40.0 W	22-24 V/DC	127 mm	43 mm	28 mm	€ 29.95
<b>862201</b>	1050 mA	20.0-40.0 W	19-38 V/DC	127 mm	43 mm	28 mm	€ 29.95

