



DEKO-LIGHT POWER SUPPLY UNITS CC DIM | BASIC DESIGN

- can be dimmed using trailing-edge phase dimmers
- flicker-free
- short circuit, overload and overheating protection

Housing	Plastic	Mounting Location	Inside
Rated Input Voltage	220-240 V/AC		

Article	Output Current	Power	Output Voltage	Length	Width	Height	Price
862202 ■	350 mA	3.9-9.0 W	11-26 V/DC	115 mm	39 mm	22 mm	€ 28.95
862203 ■	350 mA	6.3-12.0 W	19-38 V/DC	115 mm	39 mm	22 mm	€ 36.95
862204 ■	350 mA	9.8-20.0 W	28-57 V/DC	127 mm	44 mm	28 mm	€ 39.95
862205 ■	500 mA	10.0-20.0 W	20-40 V/DC	127 mm	44 mm	28 mm	€ 39.95
862136 ■	500 mA	20.0-40.0 W	40-80 V/DC	166 mm	52 mm	24 mm	€ 46.95
862207 ■	700 mA	9.8-22.0 W	14-35 V/DC	127 mm	44 mm	28 mm	€ 39.95
862208 ■	700 mA	19.0-40.0 W	28-56 V/DC	166 mm	52 mm	24 mm	€ 46.95
862264 ■	900 mA	19.6-40.0 W	22-44 V/DC	166 mm	52 mm	25 mm	€ 46.95
862209 ■	1050 mA	20.0-40.0 W	19-38 V/DC	166 mm	55 mm	25 mm	€ 46.95
862210 ■	1050 mA	23.0-45.0 W	22-43 V/DC	166 mm	52 mm	25 mm	€ 49.95
862211 □	1300 mA	25.0-50.0 W	20-39 V/DC	166 mm	55 mm	25 mm	€ 51.95



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.