



HEP POWER SUPPLY UNIT CC DIM | G6LT15W350LR-Z

- Dimmable with trailing edge phase dimmers
- Flicker-free
- Short-circuit and overload-proof
- overheating protection

Housing	Plastic	Width	40.4 mm
Output Current	350 mA	Height	22 mm
Power	9.1-15 W	Rated Input Voltage	220-240 V/AC
Output Voltage	26-43 V/DC	Mounting Location	Inside
Length	85 mm		

Article Price

862266 € 32.95



DEKO-LIGHT POWER SUPPLY UNITS CC DIM | BASIC MULTI-CURRENT

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Short-circuit-proof, overload protection, overheating protection

Housing	Plastic	Height	28.5 mm
Length	150 mm	Rated Input Voltage	200-240 V/AC
Width	42.5 mm	Mounting Location	Inside

Article Price

Article	Price	Technical Description
862141 <input type="checkbox"/>	€ 41.95	350 mA/3.2-14.0 W/9-40 V 400 mA 3.60-16.00 W/9-40 V 450 mA 4.00-18.00 W/9-40 V 500 mA 4.50-20.00 W/9-40 V 550 mA 5.00-19.80 W/9-36 V 600 mA 5.40-19.80 W/9-33 V 650 mA 5.90-19.50 W/9-30 V 700 mA 6.30-19.60 W/9-28 V

