



### MEANWELL POWER SUPPLY UNITS CC DIM | MULTI LCM DALI

- can be dimmed using DALI2, DALI1 or Intelli-Push (Touch-Dim via 230 V button)
- Current range adjustable using DIP switch
- can be operated without actuation/dimming
- flicker-free

Housing	Plastic	Mounting Location	Inside
Height	23 mm		

Article	Technical Description	Length	Width	Rated Input Voltage	Price
<b>862247</b> <input type="checkbox"/>	350 mA / 0.7-35.0 W / 2-100 V 500 mA / 1.0-40.0 W / 2-80 V 600 mA / 1.2-40.0 W / 2-67 V 700 mA / 1.4-40.0 W / 2-57 V 900 mA / 1.8-40.5 W / 2-45 V 1,050 mA / 2.1-42.0 W / 2-40 V	123.5 mm	81.5 mm	180-295 V/AC	<b>€ 104.95</b>
<b>862246</b> <input type="checkbox"/>	350 mA / 2.1-18.9 W / 6-54 V 500 mA / 3.0-25.2 W / 6-50 V 600 mA / 3.6-25.2 W / 6-42 V 700 mA / 4.2-25.2 W / 6-36 V 900 mA / 5.4-25.2 W / 6-28 V 1,050 mA / 6.3-25.2 W / 6-24 V	105 mm	68 mm	180-277 V/AC	<b>€ 89.95</b>
<b>862248</b> <input type="checkbox"/>	500 mA / 1.0-45.0 W / 2-90 V 600 mA / 1.2-54.0 W / 2-90 V 700 mA / 1.4-60.3 W / 2-86 V 900 mA / 1.8-60.3 W / 2-67 V 1,050 mA / 2.1-59.9 W / 2-57 V 1,400 mA / 2.8-59.0 W / 2-42 V	123.5 mm	81.5 mm	180-295 V/AC	<b>€ 109.95</b>

