



### TRIAC-DIMMER TRAILING EDGE

suitable for dimming:

- **R loads (light bulb) 10-350 W**
- **C loads (electrical control gear) 10-350 W**
- **max. five control gears**
- **adjustable minimum load/brightness**
- **perfectly matched to DEKO-LIGHT power supply units**
- **suitable for 68 mm flush-mounted/cavity wall sockets**

Housing	Plastic	Power	355 W
Length	83.5 mm	Control	Trailing-edge dimmer
Width	83.5 mm		
Height	43.5 mm	Rated Current	1.6 A
Rated Input Voltage	220-240 V/AC	Connection Type	Clamp

Article	Housing Color	Price
---------	---------------	-------

<b>930060</b>	White	<b>€ 66.95</b>
---------------	-------	----------------



### HIGH FREQUENCY MOTION SENSOR | MD1200

- **Detection angle: 360°**
- **Detection range: 1-10 m**
- **Switching time: 5 sec.-30 min.**
- **Daylight threshold value: 5-2,000 lux**
- **Suitable for switching all standard lamps/ballasts [RLC loads]**
- **Max. five ballasts**

Housing	Plastic	Rated Input Voltage	220-240 V/AC
Length	75 mm	Power	1200 W
Width	42 mm	Connection Type	Clamp
Height	28 mm		

Article	Housing Color	Price
---------	---------------	-------

<b>930036</b>	<input type="checkbox"/> White	<b>€ 39.95</b>
---------------	--------------------------------	----------------

